

AG29-CBRS MIMO 2 x LTE 3.5GHz Omni Directional Antenna w/Bracket Mount MIMO 2 x CBRS LTE Band 48	
CBRS Compliant	CBRS Band 48
CBRS LTE Frequency Range	3550-3700MHz
Peak Gain: Isotropic (dBi)	(6dBi) 3550-3700MHz
Horizontal Half Power Beamwidth	360° / 360°
Vertical Half Power Beamwidth	70° / 35°
VSWR	≤2.0 / ≤2.0
Impedance	50 Ohms
Polarization	MIMO 2 x Vertical Omni Directional
Max. Power	50W
Dimensions	Height: 8" / 206mm - Diameter: 3" / 78mm
Radome	High Impact Polycarbonate
Operating Temperature	40° to 158° (°F)
Wind Velocity	140 MPH
Ingress Protection	IP67
Mounting Mast Diameter	1.5"~2" / 40mm~50mm
Net Weight	1.5bs / 0.7kg Includes mounting hardware
Coax Cable Options (Finished)	2 x 16ft CFD200 Coax Cables – 2 x SMA Male 2 x 1ft CFD200 Coax Cables – 2 x N Female
Mount Type	Includes Mounting Hardware L-Bracket Mount + 2 x U-Bolt Sets

78mm
3"

206mm
8"



Includes
L-Bracket Mount
2 x U-Bolt Sets