

AG79 MIMO 4 x Cellular 4G LTE CBRS 5G NR WiFi 6 Omni Directional Antenna w/Bracket Mount
 Wide-Band Multi-MIMO 4 x Cellular 4G LTE CBRS 5G NR / WiFi 6 2.4GHz~6GHz

Multi-Carrier / Multi-Technology 4G LTE CBRS 5G NR Compliant	Verizon 4G 5G (DSS) Bands: B2 B4 B5 B13 B46 B48 B66 T-Mobile 4G 5G Bands: B2 B4 B5 B12 B25 B26 B41 B66 B71 n25 n41 n66 n71 AT&T 4G 5G Bands: B2 B4 B5 B12 B14 B17 B29 B30 B66 n5 5G NR Bands: n77 n78 CBRS Band: B48
4G CBRS 5G NR Frequency Range WiFi 6 Frequency Range	617-960MHz / 1710-6000MHz 2.4GHz~6GHz
4G 5G NR Avg Peak Gain: Isotropic WiFi 6 Avg Peak Gain: Isotropic	(5dBi) 617~960MHz / (6dBi) 1710~3600MHz / (7dBi) CBRS 3550~3700MHz (7dBi) 2.4GHz~2.5GHz / (5dBi) 5GHz~6GHz
Horizontal Half Power Beamwidth	360° / 360°
Vertical Half Power Beamwidth	60° / 40°
VSWR	≤2.0 / ≤2.0
Impedance	50 Ohms
Polarization	Multi-MIMO 4 x Vertical / Omni Directional
Max. Power	50W
Dimensions	Height: 35.4" / 900mm - Diameter: 3.4" / 85mm
Radome	Fiberglass
Operating Temperature	-40° to 158° (°F)
Wind Velocity	135 MPH
Ingress Protection	IP67
Mounting Mast Diameter	2"~3.5" / 50mm~90mm
Net Weight	7lbs / 3.2kg <i>Includes mounting hardware</i>
Connector Type	4 x 1ft CFD200 Pigtailed / 4 x N Female Connector Ends <i>Extension Cables Sold Separately</i>
Mount Type	Includes Mounting Hardware Bracket Mount + 2 x U-Bolt Sets

900mm
35.4"



Includes
Aluminum
Mounting Bracket

4 x CFD200
1ft Coax Cables

Includes
2 x U-Bolt Sets



4 x N Female
Connector Ends

