

Private Networks: Anterix / CBRS / LoRaWAN / WiFi HaLow Includes: Bracket Mount / Outside Use / Extension Coax Cables Available

AG39 2-Lead Cellular / WiFi Omni MIMO Series M2M IoT Antenna Specifications Multi-Network Omni Directional MIMO 2 x Cellular 4G LTE 5G NR / WiFi 6 Private Networks: Anterix / CBRS / LoRaWAN / WiFi HaLow Includes Mounting Hardware / Extension Coax Cables Available

Private N	Iletworks: Anterix / CBRS / LoRaWAN / WiFi HaLow Mounting Hardware / Extension Coax Cables Available
Frequency Range: 4G LTE 5G NR Anterix / LoRaWAN / WiFi HaLow / CBRS WiFi 6	617-960MHz / 1710-6000MHz 896~940MHz / 902~928Mhz / 3550-3700MHz 2.4GHz / 5GHz
Avg Peak Gain Isotropic: 4G LTE 5G NR Anterix LoRaWAN WiFi HaLow CBRS WiFi 6	(7dBi) 617-960MHz / (9dBi) 1710-3800MHz / (9dBi) 4900-6000MHz (7dBi) 896~940MHz / (7dBi) 902~928Mhz / (9dBi) 3550-3700MHz (9dBi) 2.4GHz / (9dBi) 5GHz
Typical Efficiency – <i>Elements</i>	617-960MHz >50% 1710-3800MHz >50% 4900-6000MHz >55%
Isolation:- Elements	>10dB
Correlation Co-efficient – Elements	<0.2
Horizontal Half Power Beamwidth	360° / 360°
Vertical Half Power Beamwidth	40° / 25°
VSWR	≤2.0 / ≤2.0
Nominal Impedance	50Ω
Polarization	MIMO 2 x Vertical Omni Directional
Max. Power	50W
Mechanical / Environmental Specifications	
Application	Outside
Radome	High Impact Polycarbonate Height: 35" / 890mm - Diameter: 3" / 78mm
Connector Types	2 x N Female
Coax Cables	Sold Separately Extension Coax Cable Options Available (Sold Separately) All Standard Connector Ends Available (Including SMA QMA TNC FAKRA N Connector Ends)
Mounting Hardware (Stainless Steel)	Includes Mounting Hardware Bracket Mount + 2 x U-Bolt Sets
Mounting Mast Diameter	2"~3.5" / 50mm~90mm
Ingress Protection	IP69K
Wind Velocity	140 MPH
Operating Temp (°F)	-40° / +158° (°F)
Weight	3.75lb / 1.7kg





Private Networks: Anterix / CBRS / LoRaWAN / WiFi HaLow Includes: Bracket Mount / Outside Use / Extension Coax Cables Available

Multi-Network Cellular / WiFi Applications - 2 x NF		
Cellular + WiFi	Cellular 4G LTE 5G NR + WiFi Band 1-6	
MIMO Cellular	MIMO 2 x Cellular 4G LTE 5G NR	
MIMO WiFi	MIMO 2 x WiFi Band 1-6	



Supported Cellular Service Provider Networks	
Verizon Including MVNO's	Verizon 4G LTE 5G NR Bands 4G LTE: <i>B2 B4 B5 B13 B46 B48 B66</i> 5G NR: <i>N2 N5 N13 N66 N77 N79 (C-Band)</i>
T-Mobile Including MVNO's	Mobile 4G LTE 5G NR Bands 4G LTE: <i>B2 B4 B5 B12 B41 B66 B71</i> 5G NR: N2 <i>N25 N41 N71 N79 (C-Band)</i>
AT&T Including MVNO's	AT&T 4G LTE 5G NR Bands 4G LTE: <i>B2 B4 B5 B12 B14 B17 B29 B30 B48 B66</i> 5G NR: <i>N2 N5 N66 N77 N79 (C-Band)</i>
Supported Private Networks	
Anterix	Anterix 4G LTE 5G Bands (AG60 Enterprise Series Antennas are Anterix 4G 5G Ready) 900MHz Band (896-901MHz / 935-940MHz) B8 B106
CBRS	CBRS 4G LTE 5G Bands (AG60 Enterprise Series Antennas are CBRS 4G 5G Ready) 3.5GHz Band (3550-3700MHz) B48
WiFi HaLow	WiFi HaLow Bands (AG60 Enterprise Series Antennas are WiFi HaLow Ready) 900MHz Band (902-928MHz) IEEE 802.11ah
LoRaWAN	LoRaWAN 4G LTE 5G Bands (AG60 Enterprise Series Antennas are LoRaWAN Ready) 915MHz Band (902-928MHz) US915
Supported WiFi IEEE Standards	
WiFi 1-6	WiFi 1 WiF 2 (802.11ba) WiFi 3 (802.11g) WiFi 4 (802.11n) WiFi 5 (802.11ac) WiiFi 6 6E (802.11ax)
* WiFi HaLow	WiFi HaLow (802.11ah) * Contact Us For AG45 Series HaLow WiFi Configuration Options



Private Networks: Anterix / CBRS / LoRaWAN / WiFi HaLow Includes: Bracket Mount / Outside Use / Extension Coax Cables Available

AG39 Cellular Omni MIMO Series Antenna – 2 x N Female Dimensions / Mounting Bracket



SKU: AG39-2NF



890mm

35"





Stainless Steel Mounting Bracket

Includes
Mounting Bracket
2 x U-Bolt Sets



2 x N Female Connectors





Private Networks: Anterix / CBRS / LoRaWAN / WiFi HaLow Includes: Bracket Mount / Outside Use / Extension Coax Cables Available

AGA Ultra Low-Loss Extension Coax Cables (Sold Separately)

Finished AGA195 | AGA240 | AGA400 Extension Coax Cables (Lengths: 15ft - 100ft) - N Male AG79 Extension Cable Options (N Male): SMA Male | RP SMA Male | QMA Male | RP TNC Male | TNC Male



SMA Male



RP SMA Male



QMA Male



RP TNC Male



TNC Male







Private Networks: Anterix / CBRS / LoRaWAN / WiFi HaLow Includes: Bracket Mount / Outside Use / Extension Coax Cables Available

AGA Ultra Low-Loss Extension Coax Cables / 1ft AGA200 Adapter Cables (Sold Separately)

Finished AGA195 | AGA240 | AGA400 Extension Coax Cables (Lengths: 15ft - 100ft) - N Male / N Male








Private Networks: Anterix / CBRS / LoRaWAN / WiFi HaLow Includes: Bracket Mount / Outside Use / Extension Coax Cables Available

System Lightning Surge Protection Kits / Ground Kits / J-Pipe Mount (Sold Separately)



Surge Protector w/ L-Bracket Mount Kit SKU: AGA-LSP-NF-LBM



Surge Protector w/ L-Bracket Mount Kit SKU: AGA-LSP-SF-LBM









